


TSic[™]101/106/201/206/301/306/506
Rapid Response, Low-Cost Temperature Sensor IC
with Analog or digital Output Voltage

Data Sheet
Rev. 3.7 / April 2010



TSic™ 101/106/201/206/301/306/506

Brief Description

The TSic™ temperature sensor IC family are fully tested and calibrated sensors with absolute measurement accuracy on delivery, no further calibration needed.

The TSic™ combines outstanding accuracy with long term stability, yet it is very simple to use. The TSic™ series is specifically designed for high performance, cost-effective solutions for sensing temperature in building automation, automotive, industrial, office automation, white goods and low-power/mobile applications.

TSic™ employs a high precision bandgap reference with PTAT output; a low-power, precision ADC; and an on-chip DSP core with EEPROM to precisely calibrate the output temperature signal.

The TSic™ series includes ICs with two linear analog signal output options, such as standard 0~1V_{out} (Supply voltage (V₊) = 3.0V to 5.5V) or ratiometric (10~90% of supply voltage); or the digital serial output signal for interfacing with microcontrollers.

Standard TSic™ devices are available with digital (ZacWire, TSic™x06) or analogue (0-1V, TSic™x01) output Signal.

Features

- Low cost, precision temperature sensor
- Analog 0 to 1 Volt signal output¹⁾
- Resolution: 0.1°C (0.034°C TSic™506)
- Single-wire 11-bit digital serial signal output²⁾
- Communication range > 10 meters²⁾
- Accuracy: up to ±0.1°C over span of 40°C
- Wide measurement range:
 - 50 to +150 °C (TSic™ 10x/20x/30x)
 - 10 to +60 °C (TSic™ 506)
- Signal read-out every 0.1s (other rates available on request)
- Supply Voltage 3.0V to 5.5V; high accuracy operation in range 4.5V to 5.5V¹⁾
- Package: 8-pin SOP, 3-pin TO-92, Die on Wafer
- Low quiescent current to minimize self-heating and power consumption (45µA typ.)

- System-on-chip based on advanced mixed-signal CMOS technology integrating precision temperature sensing bandgap reference with proportional-to-absolute-temperature (PTAT) output, digital signal processor (DSP) core, and electrically erasable memory (EEPROM)

Benefits

- Several accuracy classes available with 100% upward compatibility
- No calibration by customer needed; absolute calibration specified
- Simple to integrate, reducing cost and time for application-development
- Fast data measurement – optimal for temperature control
- Packages for standard SMD, THT or application specific assembly
- Very low power consumption – ideal for mobile and standard applications
- Field reconfiguration/recalibration option available (high volume customers only)

Available Support


For TSic™ evaluation ZMDI provides a special Evaluation Tool. (*Ordering Code: TSic Lab Kit*)

Further application support is available through the hotline:

email: micsensor@yeah.net

Phone: +86 523 8815 5558

TSic™ 101/106/201/206/301/306/506 Overview



- 1) For TSic™ with analog output only (TSic™101/201/301)
- 2) For TSic™ with digital output only (TSic™106/206/306/506)

TSic™101/106/201/206/301/306/506

Contents

Contents.....	3
List of Figures	4
List of Tables.....	4
1 Electrical Characteristics	5
1.1. Absolute Maximum Ratings	5
1.2. Operating Conditions	5
2 Accuracy of Temperature Measurement.....	6
3 Output Examples for TSic™101/106/201/206/301/306/506.....	7
4 Lifetime for TSic™101/106/201/206/301/306/506 Devices.....	7
5 Pin configuration and Package	8
5.1. Pin Configuration.....	8
5.2. Package Outline.....	10
6 Additional Documents	13
7 Document Revision History	13

TSic™101/106/201/206/301/306/506

List of Figures

Figure 2-1	Accuracy Overview TSic™ Family.....	6
Figure 5-1	TSic™101/106/201/206/301/306/506 Pin Diagram SOP8	8
Figure 5-2	TSic™101/106/201/206/301/306/506 Pin Diagram TO-92.....	9
Figure 5-3	SOP 8 Package dimensions	10
Figure 5-4	TO-92 Package dimensions.....	11
Figure 5-5	Bare Die Dimensions	12

List of Tables

Table 1-1	Absolute Maximum Ratings	5
Table 1-2	Operating Conditions.....	5
Table 2-1	Accuracy TSic™101/106/201/206/301/306/506 ¹⁾	6
Table 3-1	Output Examples for TSic™101/106/201/206/301/306/506	7
Table 4-1	Output Examples for TSic™101/106/201/206/301/306/506	7
Table 5-1	TSic™101/106/201/206/301/306/506 PIN Diagram SOP8.....	8
Table 5-2	TSic™101/106/201/206/301/306/506 PIN Diagram TO-92	9
Table 5-3	SOP 8 Package dimensions [mm]	10
Table 5-4	TO-92 Package dimensions [mm].....	11
Table 5-5	TSic™101/106/201/206/301/306/506 PIN Diagram Bare Die	12

TSic™101/106/201/206/301/306/506

1 Electrical Characteristics

1.1. Absolute Maximum Ratings

Table 1-1 Absolute Maximum Ratings

Symbol	Parameter	Min	Max	Unit
V+	Supply Voltage	-0.3	6.0	V _{DC}
V _{INA} , V _{OUTA}	Voltages at analog I/O – Pins	-0.3	V _{DDA} +0.3	V _{DC}
T _{Stor}	Storage temperature	-50	150	°C

1.2. Operating Conditions

Table 1-2 Operating Conditions

Symbol	Parameter	Min	Typ	Max	Unit
V+	Supply ¹⁾ Voltage to Gnd	3.0	5.0	5.5	V
I _{V+}	Supply Current ²⁾³⁾ @ V+ = 3.3V, RT			200	μA
I _{V+}	Supply Current ²⁾⁴⁾ @ V+ = 3.3V, RT	30	45	80	μA
T _{amb}	Ambient Temperature ⁵⁾ Range	-50		150	°C
C _{V+}	External Capacitance between V+ and GND ⁶⁾ (C _{V+})	80	100	470	nF
C _L	Output Load Capacitance (C _L) ⁴⁾			15	nF
	Output Load Resistance between signal and GND (or V+) ³⁾	47	100		kΩ
	Output Load Resistance between signal and GND (or V+) ⁴⁾	1			MΩ

1) Best accuracy with supply voltage 4.5V – 5.5V. With supply voltage 3.5V – 4.5V(TSic™101/201/301) 3.5V – 4.5V (TSic™106/206/306/506) accuracy reduced

2) Without load

3) For TSic™ with analog output only (TSic™101/201/301)

4) For TSic™ with digital output only (TSic™106/206/306/506)

5) Output signal is limited to this ambient temperature ±3°C (with regard to calibration, offset and gain)

6) Recommended as close to TSic V+ and GND-Pins as possible

TSic™101/106/201/206/301/306/506

2 Accuracy of Temperature Measurement

The accuracy describes the specification plus quantization error of 1 bit (0.1°C). This device gets calibrated at a supply voltage of 5V. For applications which require the best accuracy at a supply voltage of 3V the possibility to create a customer specific 3V calibrated device exists. Other TSic™ products with customer specific calibration are available on request (i.e. with special calibration where the 80°C span (bandgap) with the high precision temperature range of ±0.5 °C is shifted to another (lower or higher) temperature range).

Figure 2-1 Accuracy Overview TSic™ Family




Table 2-1 Accuracy TSic™101/106/201/206/301/306/506¹⁾

Product Version	Resolution	T-Range 3					
		T-Range 2				T-Range 3	
		T-Range 1		T-Range 2		T-Range 3	
		T-Range 1	Accuracy 1	T-Range 2	Accuracy 2	T-Range 3	Accuracy 3
TSic 101/106	0.1°C	+15°C to +25°C	<±0.5°C	+0°C to +40°C	<±1.0°C	-50°C to +150°C	no limits (typ ±1.5°C)
TSic 201/206	0.1°C	+10°C to +90°C	<±0.5°C	-20°C to +110°C	<+0.95°C >-0.5°C	-50°C to +150°C	<+2.0°C >-0.5°C
TSic 301/306	0.1°C	+10°C to +90°C	<±0.3°C	-20°C to +110°C	<+0.95°C >-0.3°C	-50°C to +150°C	<+2.0°C >-0.5°C
TSic 506	0.034°C	+5°C to +45°C	<±0.1°C	-5°C to +55°C	<+0.2°C >-0.1°C	-10°C to +60°C	<+0.3°C >-0.1°C

1) Accuracy for supply voltage within V+ = 4.5V to 5.5V

TSic™101/106/201/206/301/306/506

3 Output Examples for TSic™101/106/201/206/301/306/506

Table 3-1 Output Examples for TSic™101/106/201/206/301/306/506

Temp (°C)	Temp (°F)	Analog 0~1V (TSic™ 101/201/301) ¹⁾⁴⁾	Digital (TSic™ 106/206/306) ¹⁾³⁾	Digital (TSic™ 506) ²⁾³⁾
-50	-58	0.000	0x000	-
-10	14	0.200	0x199	0x000
0	32	0.250	0x200	0x124
25	77	0.375	0x2FF	0x3FF
60	140	0.550	0x465	0x7FF
125	257	0.875	0x6FE	-
150	302	1.000	0x7FF	-

1) Temperature Measurement Range -50(LT)°C to 150(HT)°C or -58°F to 302°F (Wide Range Device)
 2) Temperature Measurement Range -10(LT)°C to 60(HT)°C or 14°F to 140°
 3) Temperature = (Digital_signal/2047*(HT-LT)+LT) [°C]
 4) Temperature = (Sig[Volt]*(HT-LT)+LT) [°C]

4 Lifetime for TSic™101/106/201/206/301/306/506 Devices

Table 4-1 Output Examples for TSic™101/106/201/206/301/306/506

Operating Temperature	expected Lifetime
140°C...150°C	min. 1500h
125°C...140°C	min. 3000h

TSic™101/106/201/206/301/306/506

5 Pin configuration and Package

5.1. Pin Configuration

Available packages for the TSic™101/106/201/206/301/306/506 is are SOP8 and TO92 package.

Figure 5-1 TSic™101/106/201/206/301/306/506 Pin Diagram SOP8




Table 5-1 TSic™101/106/201/206/301/306/506 PIN Diagram SOP8

Pin	Name	Description
1	V+	Supply voltage (3.0-5.5V)
2	Signal	Temperature output signal
4	GND	Ground
3, 5-8	TP/NC	Test pin / NC Do not connect

TSic™101/106/201/206/301/306/506

Figure 5-2 TSic™101/106/201/206/301/306/506 Pin Diagram TO-92




Table 5-2 TSic™101/106/201/206/301/306/506 PIN Diagram TO-92

Pin	Name	Description
1 ¹⁾	GND	Ground
2	Signal	Temperature output signal
3 ¹⁾	V+	Supply Voltage (3.0-5.5V)

1) The e-line package (discontinued) has swapped pins 1 and 3

TSic™101/106/201/206/301/306/506

5.2. Package Outline

Figure 5-3 SOP 8 Package dimensions




Table 5-3 SOP 8 Package dimensions [mm]

	min	max
A	1,55	1,95
A ₁	0,1	0,3
A ₂	1,4	1,8
b _P	0,35	0,49
c	0,15	0,25
D	4,8	5
E	3,8	4,0
e _{nom}	1,27	
H _E	5,8	6,3
k	0,3	
L _P	0,4	
θ	0°	8°
Z	0,635	

TSic™101/106/201/206/301/306/506

Figure 5-4 TO-92 Package dimensions




Table 5-4 TO-92 Package dimensions [mm]

	min	max
A	2,16	2,41
a	1,10	1,20
b	0,41	0,495
c	0,41	0,495
D	3,61	4,01
E	4,37	4,77
e	1,27	
L	13,0	13,97

TSic™101/106/201/206/301/306/506

Figure 5-5 Bare Die Dimensions




Table 5-5 TSic™101/106/201/206/301/306/506 PIN Diagram Bare Die

Pin	Name	X Coordinate [µm]	Y Coordinate [µm]	Notes
VSSd	GND	215.8	1371.9	VSS must be connected.
VSSa	GND	356.2	1371.9	VSS analog must be connected.
Signal	Signal	524.9	1371.9	SIG™
VDD	V+	851.5	1371.9	VDD must be connected.
VDDa	V+	996.9	1371.9	VDD analog must be connected.

TSic™101/106/201/206/301/306/506

6 Additional Documents

Document

ZACWire Technical Note

PCN

TSic™ Ordering Guide

File Name

IST_TSic_ZACwire_Vx.x Digital Output_xdatex.pdf

PCN_eline_Jan07.pdf

TSic_Ordering_Guide_Rev.x.x.pdf

Visit ZMDI's website www.mic-sensor.com or contact your nearest sales office for the latest version of these documents.

7 Document Revision History

Revision	Date	Description
3.5	August 11, 2006	Update after review
3.6	June 12, 2007	Update after review
3.7	November 7, 2008	- Combination of documents: datasheet TSic™ 10x to 50x and Packaging information - changes in Pin configuration and Package

TSic™101/106/201/206/301/306/506

Sales and Further Information

www.mic-sensor.com

Zentrum Mikroelektronik Dresden AG (ZMD AG) Grenzstrasse 28 01109 Dresden Germany Phone +49 (0)351.8822.7.772 Fax +49(0)351.8822.87.772	ZMD America, Inc. 8413 Excelsior Drive Suite 200 Madison, WI 53717 USA Phone +01 (608) 829-1987 Fax +01 (631) 549-2882	ZMD AG, Japan Office 2nd Floor, Shinbashi Tokyu Bldg. 4-21-3, Shinbashi, Minato-ku Tokyo, 105-0004 Japan Phone +81.3.6895.7410 Fax +81.3.6895.7301	ZMD Far East, Ltd. 3F, No. 51, Sec. 2, Keelung Road 11052 Taipei Taiwan Phone +886.2.2377.8189 Fax +886.2.2377.8199
---	---	---	--

DISCLAIMER: This information applies to a product under development. Its characteristics and specifications are subject to change without notice. Zentrum Mikroelektronik Dresden AG (ZMD AG) assumes no obligation regarding future manufacture unless otherwise agreed to in writing. The information furnished hereby is believed to be true and accurate. However, under no circumstances shall ZMD AG be liable to any customer, licensee, or any other third party for any special, indirect, incidental, or consequential damages of any kind or nature whatsoever arising out of or in any way related to the furnishing, performance, or use of this technical data. ZMD AG hereby expressly disclaims any liability of ZMD AG to any customer, licensee or any other third party, and any such customer, licensee and any other third party hereby waives any liability of ZMD AG for any damages in connection with or arising out of the furnishing, performance or use of this technical data, whether based on contract, warranty, tort (including negligence), strict liability, or otherwise.



中创信晟（泰州）传感技术有限公司