


Technical Data

Resistance at 0°C (R ₀)	20 Ω	
Temperature coefficient (0°C up to +100°C)	3.85 · 10 ⁻³ K ⁻¹	
Tolerance classes according to DIN EN 60751	<ul style="list-style-type: none"> • F 0,3 (-50°C - +500°C) • F 0,6 (-50°C - +600°C) 	
Operating temperature range depending on lead material:		
AgPd5	-50 °C up to +400 °C	
Pt-coated Ni-wire(NiPt)	-50 °C up to +500 °C (short-time up to +550 °C)	
Pt	-50 °C up to +600 °C	
Measurement current (DC) at 25 °C	1.0 mA	
Maximal permissible peak current (DC) at 25 °C	3.0 mA	
Insulation resistance	> 10 MΩ	
Self-heating at 0 °C	< 0.5 K / mW	
Thermal response time		
Flowing water (v = 0.2 m/s)	T _{0.5} = 0.07s, T _{0.9} = 0.2s	
Flowing air (v = 1 m/s)	T _{0.5} = 4 s, T _{0.9} = 10 s	
Resistance value [Ω] at		
Temperature	Tolerance class	
	F 0,3 [Ω]	F 0,6 [Ω]
0 °C	20 ± 0.023	20 ± 0.023
+100 °C	27.702 ± 0.061	27.702 ± 0.121
R _t measuring point	2 mm from wire end	

Maximal Resistance Change at UCT 250 h	< 0.1 %						
Specification	DIN EN 60751						
Type	Film sensor						
Technology: Advanced thin-film-technology (ceramic carrier with a structured platinum layer, covered with a passivating layer)							
Operating conditions: Unprotected application only in dry environments without any contamination							
Conformity: 2011/65/EU: Restriction of the use of Hazardous Substances Directive (RoHS)							
Dimensions [mm]							
	Pt20 FMC 0.8x5x0.7 axial	Pt20 FMC 0.8x5x1 axial	Pt20 FMC 0.8x5x1.3 axial	Leads	AgPd5	NiPt 1)	Pt
H1 [mm]	0.7 ± 0.2	1 ± 0.2	1.3 ± 0.2	l [mm]	15 ± 1	10 ± 1	7 ± 1
H2 [mm]	0.27	0.4	0.65	d [mm]	0,15	0,15	0,15
1) not available with H1 = 0.7 mm and H2 = 0.27 mm							

Functional performance

according to DIN EN 60751



Picture 1: Resistance and temperature tolerances of Pt20 (Please note - the operating temperature range depends on lead material!)

Temperature range from -50 °C up to 0 °C:

$$R_t = R_0 \cdot (1 + A \cdot t + B \cdot t^2 + C \cdot (t - 100 \text{ °C}) \cdot t^3)$$

Temperature range from 0°C up to +600°C:

$$R_t = R_0 \cdot (1 + A \cdot t + B \cdot t^2)$$

Tolerance classes according to DIN EN 60751:

Class F 0,3 (-50°C - +500°C): $\Delta t = \pm (0.3 + 0.005 \cdot |t|)$

Class F 0,6 (-50°C - +600°C): $\Delta t = \pm (0.6 + 0.01 \cdot |t|)$

Whereby:

R_t ... Resistance [Ω] at temperature t

R₀ ... Resistance [Ω] at 0 °C

t ... Temperature [°C]

Δt ... Permissible temperature deviation at t [°C]

$$A = 3.9083 \cdot 10^{-3} \text{ °C}^{-1}$$

$$B = -5.775 \cdot 10^{-7} \text{ °C}^{-2}$$

$$C = -4.183 \cdot 10^{-12} \text{ °C}^{-4}$$



Fields of application

- Industrial electronics
- Building automation
- Automotive electronics
- Energy and environmental engineering
- Safety and medical engineering

Ordering examples

Construction	Class of accuracy	Leads (ø d x l [mm] lead material)	Operating temperature range [°C]
Pt20 FMC 0.8x5x1 axial	F 0,3	0.15x15 AgPd5	- 50/+400
Pt20 FMC 0.8x5x1.3 axial	F 0,3	0.15x10 NiPt	- 50/+500

Other classes of accuracy and wire lengths are available on request.



UST Umweltsensortechnik GmbH
is certified according to

